



# Data Sheet

# VIGO

## Functional LIGHT




- High Efficacy up to 80lm/W
- Powered by Epistar LED chips
- Colour rendering index Ra>80
- Extended lifetime 50,000h
- 5-years warranty
- Body color options : Black , White



## Product Specification

|                             |                                    |
|-----------------------------|------------------------------------|
| Family Name                 | VIGO                               |
| Application                 | Houses, Hotels, Offices, and Cafes |
| Mounting Type               | Recessed                           |
| Material                    | Aluminum                           |
| Body Color                  | Black / White                      |
| Power                       | 9/12/20/30W                        |
| Lumen Efficacy              | 80lm/w                             |
| Color Rendering Index (CRI) | Ra>80                              |
| Color Temperature (CCT)     | 3000K / 4000K                      |
| Ingress protection          | 20                                 |
| Rated Voltage               | 110-265V                           |
| Frequency                   | 50/60HZ                            |
| Power Factor                | >0.9                               |
| Control gear                | Built in driver                    |
| LED chip Type               | SMD                                |
| Operating Temp              | -20~+40°C                          |
| Lifetime                    | 50000H                             |
| Warranty                    | 5 Years                            |

| Code        | Power(w) | Kelvin | Body Color | D   | H   |
|-------------|----------|--------|------------|-----|-----|
| 02359001300 | 9        | 4000K  | BK         | 90  | 70  |
| 02359001302 | 9        | 3000K  | BK         | 90  | 70  |
| 02359001400 | 12       | 4000K  | BK         | 130 | 100 |
| 02359001402 | 12       | 3000K  | BK         | 130 | 100 |
| 02359001500 | 20       | 4000K  | BK         | 165 | 140 |
| 02359001502 | 20       | 3000K  | BK         | 165 | 140 |
| 02359001600 | 30       | 4000K  | BK         | 220 | 200 |
| 02359001602 | 30       | 3000K  | BK         | 220 | 200 |
| 02359001700 | 9        | 4000K  | WH         | 90  | 70  |
| 02359001702 | 9        | 3000K  | WH         | 90  | 70  |
| 02359001800 | 12       | 4000K  | WH         | 130 | 100 |
| 02359001802 | 12       | 3000K  | WH         | 130 | 100 |
| 02359001900 | 20       | 4000K  | WH         | 165 | 140 |
| 02359001902 | 20       | 3000K  | WH         | 165 | 140 |
| 02359002000 | 30       | 4000K  | WH         | 220 | 200 |
| 02359002002 | 30       | 3000K  | WH         | 220 | 200 |



### Al Nasser Group

Salah Ad Din Al Ayyubi Rd, Al Malaz,  
P.O. Box 1246 Riyadh 11431, Saudi Arabia

Tel : +966 11 4777 70 0

Fax: +966 11 4789 46 9

[www.alnassergroup.com](http://www.alnassergroup.com)