

ANNA

SMALL SIZE



E27 hexagonal lantern in classic style, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Modular construction suitable for post top, hanging and wall installation. Supplied as optional with TÜV-CB certified, long-life and efficient **LED lamps** suitable for outdoor use. Insulation class II, protection rating IP55.

*Lanterna esagonale E27 in stile classico, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idonea per il montaggio a palo, a sospensione o a parete. Fornita anche completa di **lampadine LED** adatte ad uso in ambiente esterno, certificate TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP55.*

6,5W 800 lm	8,5W 920 lm	11W 1200 lm
2700 K	2700 K	4000 K 6500 K
+80°C -30°C	90% HUMIDITY	VOLTAGE SURGE RESISTANT
INDOOR & OUTDOOR USE		

E22.110.V1K



MADE IN ITALY

ANNA - LANTERN COMPONENTS

IP55
⚡ ⚠ ⚠







Decorative **PINNACLE** to be mounted on the roof top for post installation or on the lantern base for hanging installation.

PINNACOLO decorativo applicabile alla sommità del tetto (montaggio a palo) o sulla base della gabbia (montaggio a sospensione).

Lantern **ROOF** made of shockproof resin material, UV rays stabilized and supplied with E27 lampholder. Tool-free opening for relamping and maintenance.

TETTO realizzato in resina antiurto, stabilizzata ai raggi UV, fornito completo di portalamпада E27. Rimovibile senza l'ausilio di attrezzi per manutenzione e cambio lampadina.

DIFFUSER made of UV stabilized polymethylmethacrylate (PMMA) resistant to yellowing process due to sun rays, available in clear or opal color and provided with recess for power cable supply. Made of one piece only and closed at the bottom to ensure high protection against external agents (IP 55).

DIFFUSORE in polimetilmetacrilato (PMMA) resistente al processo di ingiallimento dovuto ai raggi solari, disponibile in colore trasparente od opale e provvisto di scanalatura per il passaggio del cavo di alimentazione. Realizzato in un pezzo unico e con fondo chiuso per garantire un alto livello di protezione contro gli agenti esterni (IP 55).

CAGE made of shockproof resin material, UV-rays stabilized, rust and corrosion-free.

GABBIA realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.

ANNA
E22.000 *



Dimensions and weight

Height: 310 mm
Width: 220 mm
Depth: 192 mm
Weight: 1 Kg

Moulded colours:

Black White

Painted colours:

Antique green Antique bronze

Diffuser PMMA:

Clear Opal


E27 FILAMENT	E27 CCT SET(*)	100 - 240 V	*ADD. SUFFIX															
		<p>suitable lamps: CFL-LED max 160 mm</p> <p>E27 lampholder only .E27</p> <table border="1"> <thead> <tr> <th>LAMP</th> <th>POWER</th> <th>LUMINOUS FLUX UP TO</th> <th>COLOUR TEMP.</th> <th></th> </tr> </thead> <tbody> <tr> <td></td> <td>6,5W</td> <td>800 lm</td> <td>2700 K</td> <td>.F1R</td> </tr> <tr> <td></td> <td>8,5 W</td> <td>920 lm</td> <td>6500 K 4000 K 2700 K</td> <td>.V1K</td> </tr> </tbody> </table>	LAMP	POWER	LUMINOUS FLUX UP TO	COLOUR TEMP.			6,5W	800 lm	2700 K	.F1R		8,5 W	920 lm	6500 K 4000 K 2700 K	.V1K	
LAMP	POWER	LUMINOUS FLUX UP TO	COLOUR TEMP.															
	6,5W	800 lm	2700 K	.F1R														
	8,5 W	920 lm	6500 K 4000 K 2700 K	.V1K														
<ul style="list-style-type: none"> Perfect MATCHING WITH CLASSIC LANTERNS. SUITABLE FOR OUTDOOR USE: 100-240V driver. 360°OMNIDIRECTIONAL LIGHT. HIGH EFFICIENCY: 90% ENERGY SAVING. 	<ul style="list-style-type: none"> A60 CCT SETTABLE: 2700K/4000K/6500K. SUITABLE FOR OUTDOOR USE: 100-240V driver. EYE COMFORT opal glass. HIGH EFFICIENCY: >85% ENERGY SAVING. 	<p>6,5W filament = 60W incandescent</p> <p>8,5W CCT</p> <p>SAVE up to 89%</p>																

LED LAMPS





Comply with: EU2019/2015
EU2019/2020
Technical details on page 596.

CCT SETTABLE LED LAMP(*)



PHOTOMETRIC DATA SAMPLE

ANNA lantern clear with Fumagalli Filament Led Lamp 6,5W.

POST height 1mt
6x6mt area: average 6 lux

The photometric data for all the versions are available upon request or on our website.

CCT switch settable in three different positions, to select the desired Kelvin temperature (2700K/4000K/6500K) and get a customized ambiance.

* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

ANNA

SMALL SIZE





BISSO/ANNA

E27 lampholder	E22.131.E27
6,5W filament	E22.131.F1R
8,5W CCT set	E22.131.V1K

Pcs 18
Kg 21,2
mc 0,209

SICHEM/ANNA

E27 lampholder	E22.120.E27
6,5W filament	E22.120.F1R
8,5W CCT set	E22.120.V1K

Pcs 18
Kg 21,2
mc 0,209

ANNA
E22.000

Pcs 1
Kg 1
mc 0,011

MIKROLOT/ANNA

E27 lampholder	E22.110.E27
6,5W filament	E22.110.F1R
8,5W CCT set	E22.110.V1K

Pcs 18
Kg 21,2
mc 0,209

PORPORA/ANNA

E27 lampholder	E22.141.E27
6,5W filament	E22.141.F1R
8,5W CCT set	E22.141.V1K

Pcs 1
Kg 3,5
mc 0,024

MIZAR/ANNA resin

E27 lampholder	E22.151.E27
6,5W filament	E22.151.F1R
8,5W CCT set	E22.151.V1K

Pcs 1
Kg 2,4
mc 0,044

ALOE'.R/ANNA resin

E27 lampholder	E22.163.E27
6,5W filament	E22.163.F1R
8,5W CCT set	E22.163.V1K

Pcs 2
Kg 8
mc 0,121

ARTU'/ANNA

E27 lampholder	E22.158.E27
6,5W filament	E22.158.F1R
8,5W CCT set	E22.158.V1K

Pcs 1
Kg 9
mc 0,148

COMPANY SOLAR UP&DOWN DOWNLIGHT IN-GROUND BRICKLIGHT FLOODLIGHT BOLLARD BULKHEAD GARDEN URBAN CLASSIC URBAN MODERN POST LAMPS REFERENCES

ANNA

SMALL SIZE



E22.156.S30.F1R



E22.156.S30.F1R



E22.156.S20.V1K





ARTU' BISSO/ANNA 2+1

E27 lampholder	E22.158.S21.E27
6,5W filament	E22.158.S21.F1R
8,5W CCT set	E22.158.S21.V1K

Pcs 1
Kg 12,1
mc 0,176

ARTU' BISSO/ANNA 3+1

E27 lampholder	E22.158.S31.E27
6,5W filament	E22.158.S31.F1R
8,5W CCT set	E22.158.S31.V1K

Pcs 1
Kg 13,1
mc 0,176

GIGI BISSO/ANNA 2+1

E27 lampholder	E22.156.S21.E27
6,5W filament	E22.156.S21.F1R
8,5W CCT set	E22.156.S21.V1K

Pcs 1
Kg 14,1
mc 0,182

GIGI BISSO/ANNA 3+1

E27 lampholder	E22.156.S31.E27
6,5W filament	E22.156.S31.F1R
8,5W CCT set	E22.156.S31.V1K

Pcs 1
Kg 15,1
mc 0,182

ARTU' BISSO/ANNA 2L

E27 lampholder	E22.158.S20.E27
6,5W filament	E22.158.S20.F1R
8,5W CCT set	E22.158.S20.V1K

Pcs 1
Kg 11,1
mc 0,176

Ø 245

ARTU' BISSO/ANNA 3L

E27 lampholder	E22.158.S30.E27
6,5W filament	E22.158.S30.F1R
8,5W CCT set	E22.158.S30.V1K

Pcs 1
Kg 12,1
mc 0,176

Ø 245

GIGI BISSO/ANNA 2L

E27 lampholder	E22.156.S20.E27
6,5W filament	E22.156.S20.F1R
8,5W CCT set	E22.156.S20.V1K

Pcs 1
Kg 13,1
mc 0,182

Ø 245

GIGI BISSO/ANNA 3L

E27 lampholder	E22.156.S30.E27
6,5W filament	E22.156.S30.F1R
8,5W CCT set	E22.156.S30.V1K

Pcs 1
Kg 14,1
mc 0,182

Ø 245